

REYNOLDS®

LGP Low Ground Pressure

high flotation special application SCRAPERS

model	heaped capacities
-------	-------------------

14CS10LGP	14.0 yd³ (10,7 m ³)
16CS10LGP	16.0 yd³ (12,2 m ³)
17C12LGP	17.0 yd³ (13,0 m ³)
17CS12LGP	17.0 yd³ (13,0 m ³)



model 14CS10LGP

sand & muck soil moving with agricultural tractors

productive:

■ LGP scrapers are self-loading to excavate, transport and spread material with minimum rolling resistance and power requirements.

economical:

■ Two 43" (1,09m) wide super flotation tires eliminate mud build up between side walls. Reduced tire rutting improves equipment ground speed.

operation:

■ Reliable hydraulic controls. Tandem hitch lowers the rear scraper when front unit is raised.

"America's Preferred Scraper"

REYNOLDS®

REYNOLDS INTERNATIONAL EQUIPMENT, L.P.
P.O. Box 550, McAllen, Texas 78505-0550 USA
www.reynoldsinternational.com

REYNOLDS

LGP Low Ground Pressure high flotation special application SCRAPERS

Specifications model number	capacity		width		tires	shipping	Price Quote
	heaped	struck	cutting	transp.	rims	weight	
14CS10LGP	14.0 yd³ (10,7 m ³)	10.7 yd³ (8,1 m ³)	120" (3,05 m)	137" (3,48 m)	66x43-25 36x25	14.000 lb (6364 Kg)	
16CS10LGP	16.0 yd³ (12,2 m ³)	12.0 yd³ (9,1 m ³)	120" (3,65 m)	137" (4,14 m)	66x43-25 36x25	17.400 lb (7909 Kg)	
17C12LGP	17.0 yd³ (13,0 m ³)	13.0 yd³ (10,0 m ³)	144" (3,65 m)	163" (4,14 m)	66x43-25 36x25	17.900 lb (8136 Kg)	
17CS12LGP	17.0 yd³ (13,0 m ³)	13.0 yd³ (10,0 m ³)	144" (3,65 m)	163" (4,14 m)	66x43-25 36x25	17.900 lb (8136 Kg)	

Standard Features

Three piece cutting blade with removable center STINGER.
Height adjustable yoke hitch.
Tandem hydraulics and hitch.

Options

Even center blade for finishing.
Laser receiver mount bracket.
Drawbar assy., for the tractor.

Quick Hitch
Drawbar



Stinger Center Blade 14CS10LGP

Tractor requirements

■ hydraulics

25 GPM (95 l/min)
at 2500 PSI (175 bar) optimum

■ engine HP range

model

14CS10LGP	250-300
16CS10LGP	300-350
17C12LGP	350-400
17CS12LGP	350-400



14CS10LGP

Specifications subject to change without notice

REYNOLDS INTERNATIONAL EQUIPMENT, L.P., P.O. Box 550, McAllen, Texas 78505-0550 USA
Tel. (956) 687-7500, Fax (956) 687-3082, E mail: info@reynoldsinternational.com